

Coupe

Armless Lounge Chair



Model	CP11
Weight	22 lbs / 10 kg (No Drainage) 27 lbs / 12.2 kg (Drainage)

Dimensions	in	cm
Seat Height	17.2"	43.7
Overall Height	30"	76.2
Depth	27.3"	69.3
Width	21.7"	55.1

Finishes

See Design Guide for finish options.

Options

- Bolt-Down Plates
- Drainage
- On site Ballasting (50 lbs / 22.7 kg)

*Ballastable up to 50 lbs (22.7 kg) of dry sand and gravel. On site ballast materials not supplied by Norix.

Assembly

None required.

Fabrication & Material

One-piece, rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Enhanced UV resistant formulation suitable for both indoor and outdoor use. Rounded edges for added safety and adjustable removable glides to stabilize for un-even surfaces. Made in the U.S.A.

Warranty

5 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix® recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Performance Test Standards

- Tested to 750 lbs (340.2 kg) static load.
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items.

